

APPLICATIONS

- Professional radio networks
- Live audio broadcasting via satellite and/or internet
- Copy split programming
- On-demand broadcast
- Program and commercial insertion

FEATURES

- Internet Broadcasting
- IP and PES audio decoding
- **Datacast XD** Built-in
- Two built-in high quality stereo audio decoders
- MPEG-1 Layer II and III
- MPEC-2 AAC
- MPEG-4 AAC-LC
- SSD for local storage of audio
- **MISTiQ** compatible
- AES-67 Support
- **Net Manager** support
- **Event Manager** support
- 10 Form-A solid-state GPOs/decoder
- 1 AES outputs/decoder
- 1 PAD/ASYNCR output/decoder
- Remotely manageable over satellite & terrestrial internet
- **Production Manager** support



OPTIONS

- Record and Playback
- Professional Media Recorder (PMR)
- Livewire by Axia digital output
- Time shifting

MAP PRO AUDIO

MAP PRO AUDIO RECEIVER DECODER

Multi-channel Receiver Decoder for Broadcast Radio

Satellite and IP distribution of radio programming with local playout of programs and ads.

The **MAP Pro Audio** Series of receiver decoders are professional are designed for satellite and IP implementations. MAP receiver decoders are fully compatible with DVB-S and DVB-S2 as well as **MISTiQ Cloud™** internet distribution. All MAP receiver decoders include IDC's **Datacast XD™** for secure addressable delivery of program and ad files.

Audio Flexibility

The **MAP Pro Audio** Series features two models: MAP PA-1CH with one audio decoder and MAP PA-2CH with two audio decoders. All the decoders have associated relays sufficient for an AM/FM co-location or AM/FM transmitter pair. Each audio decoder is independent of the other allowing maximum flexibility in data rates, codecs and sample rates: MPEG Layer II for existing DVB compatibility or MPEG Layer III or new High-Efficiency Advanced Audio Coding (HE-AAC) for the best audio performance at the lowest bit rate.

Commercial/Program Insertion

The **MAP Pro Audio** Series is specially designed to allow commercial/program insertion on any channel. **Datacast XD** client is used to download advertisement files or programs into the decoder via internet. **Copy Split** permits real-time triggering of commercials/programming overlays on a receiver by receiver basis and can be done in an event or time scheduled manner.

Enhanced Monitoring and Control

A browser-based status and control GUI allows satellite carrier frequency, data rates, port authorization, audio configuration and other operating functions to be set locally or remotely. Receivers can also be remotely controlled using IDC's **Net Manager™** and/or IDC's **Production Manager™** via satellite or the internet, individually, in groups or globally. Remote monitor and control is provided by SNMP.

Integrated Hard Drive

A SS hard drive comes built-in to each **MAP** decoder. The SSD provides for store & forward data storage plus enables the addition of a full suite of standard software modules as well as customer-specific applications.

Headend Management

The **MAP Pro Audio** Series can be managed at the headend by various IDC products: **Production Manager** for content management, **Datacast XD** Server for file transmission, **Event Manager™** for synchronized trigger insertion, and **Net Manager** for network management.

TECHNICAL



MODEL	DESCRIPTION	PRIMARY INPUT INTERFACE	SECONDARY INPUT INTERFACE	NETWORK
MAP PA with 1 audio channel	<ul style="list-style-type: none"> • 1 Audio Decoder • 1 Rack Unit 	Satellite DVB-S/S2	2 x Ethernet GbE ASI input or output (option)	ST 2022-1 FEC & ST 2022-7 Seamless Protection switching
MAP PA with 2 audio channels	<ul style="list-style-type: none"> • 2 Audio Decoders • 1 Rack Unit 	MISTiQ		

RF INPUT	
Frequency Range	950 to 2150 MHz
Frequency Tuning Steps	Synthesized 1 Hz steps
AFC Range (drift tracking)	± 10% Symbol Rate up to ± 2 MHz
Maximum Input Level	-35 to -65 dBm
Connector	Type-F, female
Impedance	75 ohms, unbalanced
LNB DC Power	+ 18 VDC maximum (horizontal polarity), or + 13 VDC at 500 mA (vertical polarity) center conductor positive, short circuit protected
LNB Requirement	<ul style="list-style-type: none"> • DRO type for high data rates, stability ± 2 MHz max • PLL type for low data rates, stability ± 25 kHz max
Diagnostics	RF input signal level, Es/No (C/N), Margin to threshold, TS bit rate, Modulation, FEC, etc.
DVB-S	
FEC Type	DVB concatenated, Viterbi and Reed-Solomon
Modulation	QPSK 1/2, 2/3, 3/4, 5/6, 7/8
Roll-off	35%
DVB-S2	
FEC Type	Concatenated, LDPC and BCH QPSK 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK 2/3, 3/5, 3/4, 5/6, 8/9, 9/10 16APSK 2/3, 3/4, 4/5, 6/5, 8/9, 9/10
Roll-off	20%, 25%, 35%
Gold Code - PLS	0 to 262143
DVB-S2X (Option)	
FEC Type	Concatenated, LDPC and BCH QPSK 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9 8PSK 3/5, 2/3, 3/4, 5/6, 8/9 16APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 32APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
Roll-off	5%, 10%, 15%, 20%, 25%, 35%
Internet / MISTiQ	
Error and data loss protection	ST2022-1 Rows & Columns FEC, ST2022-7 Seamless Protection Switching, Secure Reliable Transport (SRT)
Cloud compatibility	MISTiQ, Amazon Web Services (AWS), Microsoft Azure, etc.

AUDIO — TWO OR FOUR DECODERS	
Audio Decoding Types	MPEG-1 Layers II and III MPEG-2 AAC MPEG-4 AAC MPEG-4 AAC LC MPEG-4 AAC-HE v1 & v2
Audio Transport Formats	MPEG-TS/RTP/UDP/IP/Icecast/Shoutcast
Audio Sample Rates	32, 44.21, 48 kHz 16, 22.05, 24 kHz (not all data rates supported)
MPEG Layer 2	32, 48, 56, 64, 80, 96, 112, 128, 160 192, 224, 256, 320, 384 kb/s
MPEG Layer 3	32, 40, 48, 56, 64, 80, 96, 112, 128, 160, 192, 224, 256, 320 kb/s
AAC (LD and HE)	24-320 kb/s in 8 kb/s steps
Decoding Formats	Discrete stereo, intensity coded stereo (joint stereo), single mono, dual mono
GPO	10x Form-A solid-state per decoder
Program Associated Data	1x RS-232 per decoder with UECP decoder
Audio Output-Analog	+18 dBu (software adjustable) on XLR
Audio Output-Digital	AES on XLR
Impedance	<100 ohms (into a high impedance load)
Frequency Response	+/- 0.5 dB (20 Hz to 20 kHz)
THD + N	Better than -70 dB @ 1 kHz
Crosstalk	Better than 85 dB, between decoders
Dynamic Range	Better than 80 dB (A-weighted)
Signal to Noise	Better than 90 dB
POWER REQUIREMENTS	
Supply Voltage	100 to 240 VAC, +6%, -10%, 50 or 60 Hz
Power Consumption	180 Watts maximum
PHYSICAL PARAMETERS	
Chassis	EIA - 1RU
Dimensions (H, W, D)	4.5/9.0 cm x 48 cm x 36cm (1.75/3.5" x 19" x 14")
Weight	5.4 - 6.8 kg (12 - 15 lbs.)
ENVIRONMENTAL CONDITIONS	
Operating Temperature	0° to 45° C (32° to 113° F)
Storage Temperature	-20° to 70° C (-4° to 158° F)
Humidity	Maximum 90% relative, non-condensing