

U750 Series

Ku-band Upconverters

INPUT SPECIFICATION		Options
1. Frequency range:	70 ± 20MHz or 140 ± 40MHz (check model table)	
2. Connector:	BNC	TNC
3. Impedance:	50Ω	75Ω ⁽¹⁾
4. Return loss:	≥15dB	≥20dB ⁽²⁾
OUTPUT SPECIFICATION		
5. Frequency range:	12.75 to 14.80GHz (check model table)	
6. Connector:	N-type	SMA
7. Impedance:	50Ω	
8. Return loss:	≥20dB	
9. 1dB compression point:	+10dBm	
10. Third order intercept::	+20dBm	
11. Output mute:	Front panel, parallel and serial interface	
	>90dB at max gain, >60dB at min gain	
TRANSFER CHARACTERISTICS		
12. Gain:	0 to 30dB, adjustable in 0.1dB steps	
13. Gain ripple:	over ±20MHz: ≤1dB p.t.p.	
	over output band: ≤3dB p.t.p	
14. Group delay distortion:	over ±5MHz <2ns	
	over ±20MHz <5ns	
15. Gain stability, 0°C to 50°C:	±1dB	
16. Frequency stability, 0°C to 50°C:	10 ⁻⁷	Option 2: 10 ⁻⁸ Option 3: 3 x 10 ⁻⁹
17. External reference:	10MHz, 0dBm	5MHz, 0dBm
18. Synthesiser step size:	1kHz	
19. Noise figure (full gain):	<20dB	
Spurii		
20. Image rejection:	>75dB	
21. In-band spurii (at 0dBm output):	<-60dBc	
PHASE NOISE		
22. 10Hz:	<-45dBc/Hz	
23. 100Hz:	<-70dBc/Hz	
24. 1kHz:	<-80dBc/Hz	
25. 10kHz:	<-85dBc/Hz	
26. 100kHz:	<-95dBc/Hz	
27. 1MHz:	<-110dBc/Hz	
28. Mains related:	<-60dBc	
MISCELLANEOUS		
29. Power supply:	90 to 260V, 50/60Hz, 30VA	
30. Mechanical:	1U 19" frame, 400mm deep	
31. Temperature:	Operating: 0° to 50°C	
	Storage: -40° to 85°C	
32. Relative humidity:	Operating: 0 to 90%	
	Storage: 0 to 95%	
33. Summary alarm:	NO and NC dry relay contacts via rear mounted connector	
34. Summary alarm indication:	Front panel LED	
35. Remote control:	<ul style="list-style-type: none"> • RS232 or RS422/RS485, connector D-type 9P F • Serial emulation over TCP/IP, connector RJ45 • SNMP and HTTP over TCP/IP Ethernet, connector RJ45 	

⁽¹⁾ Noise figure increases by 3dB, overall gain decreases by 3dB.

⁽²⁾ Noise figure increases by 3dB, overall gain decreases by 3dB.

MODEL TABLE

Output Frequency	Input frequency and bandwidth		
	70 ± 20MHz	140 ± 40MHz	70 ± 20MHz, 140 ± 20MHz and ±40MHz
14.0 - 14.5GHz	U750	U760	U770
12.75 - 13.25GHz	U751	U761	U771
13.75 - 14.5GHz	U753	U763	U773
13.75 - 14.8GHz	U754	U764	U774
12.75 - 13.25GHz, 13.75 - 14.5GHz	U755	U765	U775
12.75 - 13.25GHz, 13.75 - 14.8GHz	U756	U766	U776
12.75 - 14.8GHz	U757	U767	U777
12.75 - 14.5GHz	U758	U768	U778

